

u.trust Anchor PCIe

Technical Data

Imprint

Copyright 2024	Utimaco IS GmbH Germanusstr. 4 D-52080 Aachen Germany
Phone	AMERICAS +1-844-UTIMACO (+1 844-884-6226) EMEA +49 800-627-3081 APAC +81 800-919-1301
Internet e-mail	https://support.hsm.utimaco.com/ support@utimaco.com
Document Version	1.0.7
Product Version	6.0.0
Date	2024-10-22
Document No.	2023-0005
Status	PUBLISHED

All rights reserved	<p>No part of this documentation may be reproduced in any form (printing, photocopy or according to any other process) without the written approval of Utimaco IS GmbH or be processed, reproduced or distributed using electronic systems.</p> <p>Utimaco IS GmbH reserves the right to modify or amend the documentation at any time without prior notice. Utimaco IS GmbH assumes no liability for typographical errors and damages incurred due to them. Any mention of the company name Utimaco in this documents refers to the Utimaco IS GmbH.</p> <p>All trademarks and registered trademarks are the property of their respective owners.</p>
---------------------	--

Table of Contents

1 u.trust Anchor PCIe card4

1 u.trust Anchor PCIe card

Dimensions	PCI Express (PCIe) plug-in card: Length: 167.65 mm ("half" length) Height: 111.15 mm ("full" height)
Weight	420 g
Battery	3V, Lithium cell battery, Ø 24.5 mm, L = 7.7 mm, Panasonic CR2477 or equivalent
Ports	PCIe 3.x x1 USB 2.0 x2
Environmental temperature	Operation: +10 °C to +35 °C (+50 °F to +95 °F) Storage: -10 °C to +55 °C (+14 °F to +131 °F)
Humidity	10 % to 95% relative humidity, non-condensing
MTBF	174.000 hours (as specified in MIL-HDBK-217)
RoHS compliance	Yes
WEEE	National register for waste electric equipment (EAR) DE65203472
Conformity	Interference emission in accordance with EN 55022 Class B Influence of interference in accordance with EN 61000-6-2 (industry) Equipment safety in accordance with IEC 60950-1:2001/EN 60950-1:2001 (CB scheme) FCC 47 CFR Ch. 1 Part 15 Class B